


W:\2013\2013-037 Ferndale PS No 4 Upgrade\Drawg\C1.1-Cover.dwg, 6/12/2015 9:48:58 AM, cjp


CITY OF FERNDALE, WA

PUMP STATION NO. 4 UPGRADE – CITY PROJECT No. SS2014-05

VICINITY MAP - NOT TO SCALE



LOCATION MAP - NOT TO SCALE



GENERAL NOTES

- ALL WORKMANSHIP AND MATERIALS SHALL BE IN ACCORDANCE WITH CITY OF FERNDALE STANDARDS AND THE MOST CURRENT COPY OF THE STATE OF WASHINGTON STANDARD SPECIFICATIONS FOR ROAD, BRIDGE AND MUNICIPAL CONSTRUCTION (WSDOT/APWA).
- ALL APPROVALS AND PERMITS REQUIRED BY THE CITY OF FERNDALE SHALL BE OBTAINED PRIOR TO THE START OF CONSTRUCTION.
- THE CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR THE LOCATION AND PROTECTION OF ALL EXISTING UTILITIES. THE CONTRACTOR SHALL VERIFY ALL UTILITY LOCATIONS PRIOR TO CONSTRUCTION BY CALLING THE UNDERGROUND LOCATE LINE AT 1-800-332-2344 A MINIMUM OF 2 BUSINESS DAYS PRIOR TO ANY EXCAVATION.
- ALL NEW PLASTIC PIPE AND SERVICES SHALL BE INSTALLED WITH CONTINUOUS TRACER TAPE INSTALLED 8" TO 12" UNDER THE PROPOSED FINISHED SUBGRADE. THE MARKER SHALL BE PLASTIC NON-BIODEGRADABLE, METAL CORE OR BACKING MARKED WATER WHICH CAN BE DETECTED BY A STANDARD METAL DETECTOR.
- EROSION CONTROL MEASURES SHALL BE TAKEN BY THE CONTRACTOR DURING CONSTRUCTION TO PREVENT SILTATION TO EXISTING STORM DRAINAGE FACILITIES AND ROADWAYS.
- IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO HAVE A COPY OF THESE APPROVED PLANS ON CONSTRUCTION SITE AT ALL TIMES.
- ANY CHANGES TO THE DESIGN SHALL FIRST BE REVIEWED AND APPROVED BY THE PROJECT ENGINEER.
- ALL LINES SHALL BE CLEANED AND PRESSURE TESTED PRIOR TO PAVING IN CONFORMANCE WITH THE ABOVE REFERENCED SPECIFICATIONS. TESTING SHALL TAKE PLACE AFTER ALL UNDERGROUND UTILITIES ARE INSTALLED AND COMPACTION OF THE ROADWAY SUBGRADE IS COMPLETED.
- PRIOR TO BACKFILL ALL MAINS AND APPURTENANCES SHALL BE INSPECTED AND APPROVED BY THE CITY OF FERNDALE CONSTRUCTION INSPECTOR. APPROVAL SHALL NOT RELIEVE THE CONTRACTOR FOR CORRECTION OF ANY DEFICIENCIES AND/OR FAILURES AS DETERMINED BY SUBSEQUENT TESTING AND INSPECTIONS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO NOTIFY THE INSPECTOR FOR THE REQUIRED INSPECTIONS.
- ALL WORK AND MATERIALS SHALL BE GUARANTEED BY THE CONTRACTOR FOR ONE YEAR AFTER FINAL ACCEPTANCE.
- THE LOCATIONS OF ALL EXISTING UTILITIES SHOWN ON THE PLANS ARE APPROXIMATE AND NOT ALL ARE SHOWN. THE CONTRACTOR IS RESPONSIBLE TO VERIFY AND PROTECT ALL UTILITIES.
- ALL RESTORATION AND LANDSCAPING WITHIN PUBLIC OR PRIVATE PROPERTY SHALL OCCUR WITHIN THREE WEEKS OF DISTURBANCE. THIS SHALL INCLUDE, BUT NOT BE LIMITED TO, ALL LAWNS, LANDSCAPING, FENCES, GRAVEL, ASPHALT AND CONCRETE.
- THE CONTRACTOR SHALL KEEP A RECORD OF AS-BUILT INFORMATION THROUGHOUT THE ENTIRE PROJECT. THIS INFORMATION SHALL INCLUDE ALL DEVIATIONS FROM THE PLANS AND ANY OTHER INFORMATION NOT SHOWN ON THE PLANS AND THE LOCATION OF ALL SIDE SEWER CONNECTIONS TO THE MAIN LINE.
- THE CONTRACTOR SHALL REPLACE ALL MONUMENTS, RIGHT-OF-WAY MARKERS, PROPERTY STAKES, ETC. THAT ARE DISTURBED DURING CONSTRUCTION. THE CONTRACTOR SHALL USE A SURVEYOR REGISTERED IN THE STATE OF WASHINGTON TO COMPLETE ALL SURVEY WORK.

EROSION AND SEDIMENTATION CONTROL

- IT IS THE CONTRACTOR'S RESPONSIBILITY TO PREVENT POLLUTION AND EROSION IN ACCORDANCE WITH WSDOT SECTION 1.07.15. EROSION CONTROL BEST MANAGEMENT PRACTICES SHALL CONFORM TO THE CURRENT WASHINGTON DEPARTMENT OF ECOLOGY STORMWATER MANAGEMENT MANUAL.

EXISTING UTILITIES

- CONTRACTOR IS ADVISED THAT UNDERGROUND WATER, SEWER, STORM, TELEPHONE, FIBER OPTIC, AND GAS MAY BE LOCATED IN THE VICINITY OF THIS PROJECT. NO ATTEMPT WAS MADE TO SHOW ALL UTILITIES ON THE PLAN. LOCATIONS SHOWN FOR EXISTING UTILITIES ARE APPROXIMATE. OTHER UTILITIES MAY EXIST WHICH ARE NOT SHOWN ON THE PLANS.
- IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO DETERMINE THE TRUE AND CORRECT LOCATIONS OF EXISTING UTILITIES THAT MAY IMPACT THE WORK. CONTRACTOR SHALL NOTIFY ENGINEER PRIOR TO COMMENCING CONSTRUCTION IF MARKED UTILITIES APPEAR TO CONFLICT WITH PROPOSED IMPROVEMENTS. THE COST OF LOCATING, PROTECTING AND ACCOMMODATING EXISTING UTILITIES SHALL BE INCIDENTAL TO THE COST OF THE PROJECT. IF AN ACTUAL CONFLICT REQUIRES RELOCATION OF AN EXISTING UTILITY OR THE REDESIGN OF THE PROPOSED IMPROVEMENT, THE ENGINEER WILL DETERMINE IF EXTRA PAY IS WARRANTED TO ACCOMMODATE THE CHANGED OR UNFORESEEN CONDITION. MINOR HORIZONTAL OR VERTICAL ADJUSTMENTS OF THE PROPOSED IMPROVEMENTS TO AVOID CONFLICTS SHALL NOT ENTITLE THE CONTRACTOR TO EXTRA PAY.

TRAFFIC CONTROL

- CONTRACTOR IS NOT ALLOWED TO COMPLETELY CLOSE ANY STREET TO TRAFFIC. THE NUMBER OF OPEN LANES OF TRAFFIC TO BE MAINTAINED IN EACH AREA IS ONE LANE. TRAFFIC SHALL BE MAINTAINED ACCORDING TO WSDOT SECTION 1-07.23, AND THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES.

CONTROL NOTES

- BASIS OF COORDINATES:** FOUND SURFACE MONUMENT "FERN12" IN THE NORTHWEST CORNER OF SMITH ROAD AND LABOUNTY ROAD INTERSECTION 2' EAST OF CURB LINE AT THE SOUTH END OF SIDEWALK.

NORTHING = 673,760.111 USFT
EASTING = 1,222,546.506 USFT
ELEV. = 31.27'
- BASIS OF BEARINGS:** BEARINGS ARE NAD83/91 PER THE CITY OF FERNDALE SURVEY MONUMENT NETWORK OF 2001. HELD DERIVED INVERSE BETWEEN THE ABOVE-MENTIONED CONTROL POINT "FERN12" AND "FERN11" SAID BEARING BEING N 60°49'52" W, A DISTANCE OF 3355.21'. THE FOLLOWING COORDINATES WERE HELD FOR "FERN11":

NORTHING = 675,395.391 USFT
EASTING = 1,219,616.779 USFT
ELEV. = 47.47'
- BASIS OF ELEVATIONS:** ELEVATIONS ARE NGVD29 PER THE CITY OF FERNDALE SURVEY MONUMENT NETWORK OF 2001. HELD PUBLISHED ELEVATION FOR "FERN12" OF 31.27'.

SITE BENCHMARK: "FERN12"
- SITE CONTROL POINTS:**

NO.	NORTHING	EASTING	ELEVATION	DESCRIPTION
109	673643.2000	1222241.7800	18.29	SET BERNTSEN SPIKE
200	673742.1010	1222494.3148		MON DISTURBED
900	673864.6910	1222551.0011		CASED MONUMENT
901	673760.1111	1222546.5061	31.27	BSM "FERN12"
902	673701.8033	1222610.5694		CASED MONUMENT
903	673697.3295	1222597.2083		CASED MONUMENT
904	673641.2292	1222429.9737		CASED MONUMENT
905	674494.2165	1222306.0238		REBAR / CAP
906	674613.5978	1222568.9920		CASED MONUMENT
907	675395.3910	1219616.7788	47.47	BSM "FERN11"
908	673590.4221	1222062.6952		CASED MONUMENT



INDEX TO DRAWINGS


- C1.1 COVER SHEET
- C1.2 LEGEND & ABBREVIATIONS
- C2.1 EXISTING SITE PLAN
- C2.2 PROPOSED PIPING SITE PLAN
- C2.3 PROPOSED SITE GRADING AND DRAINAGE
- C2.4 TESC PLAN, DETAILS & NOTES
- C3.1 EXISTING PLAN AND PROFILE LAYOUT
- C3.2 PROPOSED PLAN AND PROFILE LAYOUT
- C4.1 DETAILS
- C4.1A DETAILS (NEW SHEET)
- C4.2 DETAILS
- S1.1 TYPICAL DETAILS
- E1 ELECTRICAL SYMBOLS AND ABBREVIATIONS
- E2 ELECTRICAL DEMOLITION
- E3 POWER PLAN AND SCHEDULES
- E4 INSTRUMENTATION AND CONTROL PLAN
- E5 ELECTRICAL ENCLOSURE ELEVATIONS
- E6 ELECTRICAL ENCLOSURE ELEVATIONS
- E7 PUMP CONTROL WIRING DIAGRAMS
- E8 PUMP WIRING DIAGRAMS
- E9 TELEMETRY PANEL WIRING DIAGRAMS
- E10 ELECTRICAL DETAILS
- E11 ELECTRICAL SCHEDULES

ADDENDA ITEMS
HAVE BEEN POSTED
TO THIS SET

CALL
TWO BUSINESS DAYS
BEFORE YOU DIG
1-800-424-5555
UTILITIES UNDERGROUND LOCATION CENTER

BID SET

WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9061
www.wilsonengineering.com



DESIGNED BY JCC
DRAWN BY CJP
CHECKED BY AVL

CITY OF FERNDALE
PUMP STATION NO. 4
COVER SHEET

DATE 4/22/2015
SCALE AS SHOWN
JOB NUMBER 2013-037

SHEET C1.1
OF 23

W:\2013\2013-037 Ferndale PS No 4 Upgrade\Drawg\Cl.2 Legend & Abbreviations.dwg, 6/12/2015 9:53:06 AM, cjp

LEGEND & ABBREVIATIONS- SIZE & SCALE MAY VARY

EXISTING HATCH PATTERNS	DESCRIPTION
	EXIST. CONCRETE
	EXIST. BUILDING
	EXIST. EARTH
	EXIST. GRAVEL
	EXIST. SAND
PROPOSED HATCH PATTERNS	DESCRIPTION
	PROP. CONCRETE
	PROP. TOP COURSE GRAVEL
	PROP. GRAVEL
	PROP. SAND
	PROP. QUARRY SPALLS

SURFACE FEATURES	DESCRIPTION
EXISTING PLAN LINETYPES	DESCRIPTION
	BRIDGE
	BUILDING LINE
	BUILDING COLUMN
	BUILDING OVERHANG
	BULKHEAD
	CONCRETE EDGE
	CREEK EDGE
	CROWN OF ROAD
	CURB
	DITCH CENTERLINE
	DECK
	DOCK
	EDGE OF SAWCUT
	EDGE OF PAVEMENT
	FENCE
	HIGH VISIBILITY FENCE
	GATE
	GRADE
	GRAVEL
	GUARDRAIL
	JERSEY BARRIER
	LAKE/POND WATER EDGE
	LIP OF CURB
	MISC SURFACE FEATURE
	MISC TRAFFIC
	PLANTER
	PATH
	RAILROAD
	RAMP (WOOD)
	RETAINING WALL
	ROAD STRIPING
	ROCKERY
	RIVERBANK/ShORELINE
	THALWAG LINE
	TOP OF BANK/SLOPE
	TOE OF BANK/SLOPE
	VEGETATION/ShRUB LINE
	WETLAND/SWAMP PERIMETER
	WETLAND BUFFER

SURFACE FEATURES	DESCRIPTION
PROPOSED PLAN LINETYPES	DESCRIPTION
	BRIDGE
	BUILDING LINE
	CONCRETE
	CURB
	DITCH CENTERLINE
	EDGE OF BIKE LANE
	EDGE OF PAVEMENT
	FENCE
	GATE
	GRAVEL
	GUARDRAIL
	JERSEY BARRIER
	LIP OF CURB
	REBAR
	RETAINING WALL
	ROCKERY
	ROAD STRIPING

UTILITIES	DESCRIPTION
EXISTING PLAN LINETYPES	DESCRIPTION
	CABLE TELEVISION (AERIAL)
	CABLE TELEVISION (BURIED)
	SURVEILLANCE CAMERA (BURIED)
	FIBER OPTIC LINE (AERIAL)
	FIBER OPTIC LINE (BURIED)
	TELEPHONE (AERIAL)
	TELEPHONE (BURIED)
	TRAFFIC SIGNAL CONDUIT LINE
	POWER (AERIAL)
	POWER (BURIED)
	UTILITY (AERIAL)
	UTILITY (BURIED)
	POWER DUCT BANK (BURIED)
	DRAIN FIELD
	SANITARY SEWER
	SANITARY SEWER (FORCE MAIN)
	STORM DRAINAGE
	CULVERT (Ø WIDTH)
	CULVERT
	RECLAIMED WATER
	IRRIGATION
	WATER
	8" WATER
	OVERFLOW
	STEAM
	GAS
	GAS TANK/STRUCTURE
	OIL
	AIR LINE
	BURIED UTILITY APPROX. EXTENTS
	MISC UTILITY (BURIED)

PROPOSED PLAN UTILITY LINETYPES	DESCRIPTION
WATER	DESCRIPTION
	WATER
	8" WATER
	IRRIGATION
	RECLAIMED WATER
	POTABLE WATER
	WATER SERVICE
	WATER STRUCTURE
	FIRE DEPARTMENT CONNECTION
	FIRE PROTECTION LINE
SANITARY SEWER	DESCRIPTION
	SEWER
	8" SEWER
	FORCE MAIN
	DRAIN FIELD
	SEWER SERVICE
	SEWER STRUCTURE

STORM DRAIN	DESCRIPTION
	STORM DRAIN - SUBJECT PIPE
	STORM DRAIN - OTHER PIPE
	STORM SERVICE
	FOOTING DRAIN
	STORM STRUCTURE

MISC. UTILITIES	DESCRIPTION
	GAS
	POWER
	TELEPHONE/COMMUNICATIONS

GRADING	DESCRIPTION
	GRADE BREAK
	SLOPE ARROWS

EROSION CONTROL	DESCRIPTION
	EROSION TRIANGULAR SILT DIKE
	EROSION CONTROL COMPOST BERM
	EROSION CONTROL MINOR CONTOUR
	EROSION CONTROL MAJOR CONTOUR
	ORANGE BARRIER FENCE
	SILT FENCE
	STRAW WATTLE
	EROSION CONTROL FLOWLINE
	STRAW BALE
	INLET PROTECTION
	CHECK DAM

DEMOLITION	DESCRIPTION
	SURFACE FEATURE OR UTILITY TO BE REMOVED
	SAWCUT
	CLEARING LIMIT
	TREE OR BUSH TO BE REMOVED


SURVEY	DESCRIPTION
PLAN LINETYPES	DESCRIPTION
	CENTERLINE (EXISTING)
	CENTERLINE (CONSTRUCTION)
	CENTERLINE (PROPOSED)
	CONTOUR (EXISTING MINOR)
	CONTOUR (EXISTING INDEX)
	HYDRO CONTOUR (EXISTING INDEX)
	CONTOUR (PROPOSED INDEX)
	CONTOUR (PROPOSED MINOR)
	CATCHLINE
	CUT LINE
	DONATION LAND CLAIM (EXIST.)
	EASEMENT (PROPOSED)
	EASEMENT (EXISTING)
	FILL LINE
	MEANDER LINE
	ORDINARY HIGH WATER LINE
	MEAN LOW LEVEL WATER LINE
	OWNERSHIP LINE
	PROPERTY LINE (RECORD OR ADJACENT)
	PROPERTY LINE
	QUARTER SECTION LINE
	RANGE/TOWNSHIP LINE
	RESERVATION/PARK/FOREST (EX)
	RIGHT-OF-WAY (EXISTING)
	RIGHT-OF-WAY (EXISTING USED)
	RIGHT-OF-WAY (PROPOSED)
	RIGHT-OF-WAY (EX. RECORD) (RECORD OR ADJACENT)
	RIGHT-OF-WAY (LIMITED ACCESS)
	RIGHT-OF-WAY (LIMITED ACCESS)
	SECTION LINE
	SETBACK LINE (EXISTING)
	SIXTEENTH SECTION LINE
	STATE/COUNTY/CORPORATE LIMIT
	VACATED RIGHT-OF-WAY
	EASEMENT (RECORD)
	RIGHT-OF-WAY CENTER (RECORD)
	DONATION LAND CLAIM (RECORD)
	MEANDER LINE (RECORD)
	PARK LINE (RECORD)
	SECTION LINE (RECORD)
	QUARTER SECTION LINE (RECORD)
	SIXTEENTH SECTION LINE (RECORD)
	STATE LINE (RECORD)
	RANGE LINE (RECORD)

PROFILE LINETYPES	DESCRIPTION
	PROFILE EX. GRND
	PROFILE FINISH GRND
	PROFILE GRID
	PROFILE VERTICAL GRID
	PROFILE EX. GROUND LEFT
	PROFILE EXISTING GROUND RIGHT
	GAS PROFILE (EXISTING)
	POWER PROFILE (EXISTING)
	RAILROAD PROFILE (EXISTING)
	SANITARY PROFILE (EXISTING)
	SANITARY PROFILE (PROPOSED)
	STORM PROFILE (EXISTING)
	TELEPHONE PROFILE (EXISTING)
	STORM PROFILE (PROPOSED)
	TV PROFILE (EXISTING)
	UTILITY PROFILE (EXISTING)
	WATER PROFILE (EXISTING)
	WATER PROFILE (PROPOSED)

MISC. SYMBOLS	DESCRIPTION
EXISTING	PROPOSED
	SOIL BORING
	MONITORING WELL
	TEST WELL
	TEST PIT
	EMBANKMENT
	MAIL BOX
	SIGN
	RIP RAP
	BOULDER
	SHRUB
	TREE (Conifer)*
	TREE (Deciduous)*
	STUMP-PLAN VIEW
	YARD LIGHT
	WELL
	PILE
	ROCKERY
	WHEEL STOP
	SPLASH BLOCK
	GAS METER
	GAS VALVE
	PAD MOUNTED TRANSFORMER
	POWER VAULT
	TRANSMISSION TOWER
	POWER METER
	GUY POLE
	UTILITY POLE
	UTILITY POLE ANCHOR
	TELE RISER
	CABLE RISER
	TELEPHONE VAULT
	STEAM MANHOLE
	PARKING METER
	POST

SANITARY SEWER SYMBOLS	DESCRIPTION
EXISTING	PROPOSED
	SAN. SEWER CLEAN OUT
	SAN. SEWER MANHOLE
STORM DRAIN SYMBOLS	DESCRIPTION
EXISTING	PROPOSED
	STORM DRAIN CB TYPE 1
	STORM DRAIN CB TYPE 2
	STORM DRAIN CB TYPE 2 W/CB LID
	STORM DRAIN WITH OVERFLOW GRATE
	STORM DRAIN CLEAN-OUT


SECTION/DETAIL CALL-OUTS



SECTION CALL OUTS: (A) REPRESENTS THE SECTION LABEL, (B) INDICATES THE SHEET ON WHICH THE SECTION APPEARS, AND (C) INDICATES THE SHEET ON WHICH THE SECTION IS CALLED OUT.

DETAIL CALL OUTS: (A) REPRESENTS THE DETAIL LABEL, (B) INDICATES THE SHEET ON WHICH THE DETAIL APPEARS, AND (C) INDICATES THE SHEET ON WHICH THE DETAIL IS CALLED OUT.

SYMBOLS	
	=DEGREES
	=PLUS/MINUS
	=DIAMETER
	=DELTA
	=CENTERLINE
	=FLOWLINE
	=PROPERTY LINE




DIRECTIONAL ABBREVIATIONS	
N	=NORTH
NE	=NORTHEAST
E	=EAST
SE	=SOUTHEAST
S	=SOUTH
SW	=SOUTHWEST
W	=WEST
NW	=NORTHWEST

WATER SYMBOLS	DESCRIPTION
EXISTING	PROPOSED
	ARV VALVE
	GLOBE VALVE, FL
	BALL CHECK VALVE, FL
	BLOW-OFF VALVE
	SWING CHECK VALVE, FL
	BUTTERFLY VALVE, FL
	HOSE BIB/SPIGOT
	DOUBLE LEAF CHECK VALVE
	PLUG VALVE
	BALL VALVE
	FLOAT VALVE
	PINCH VALVE
	PRESSURE & VACUUM RELIEF VALVE
	VACUUM RELIEF VALVE
	PRESSURE RELIEF VALVE
	PRESSURE REGULATING VALVE (SELF CONTAINED)
	BACK PRESSURE REGULATING VALVE (SELF CONTAINED)
	IN-LINE SPRING LOADED RELIEF VALVE
	CAP/PLUG
	GUARD POST
	THRUST BLOCK
	WATER METER
	FIRE DEPARTMENT CONNECTION
	WATER VALVE
	FIRE HYDRANT
	WATER MANHOLE
	POST INDICATOR VALVE
	11-1/4 BEND, MJ-FL
	22-1/2 BEND, MJ-FL
	45 BEND, MJ-FL
	90 BEND, MJ-FL
	FLXMJ ADAPTER
	COUPLER
	BLIND FLANGE
	GATE VALVE, FLxMJ
	GATE VALVE, MJ
	REDUCER, MJxFL
	REDUCER, MJ
	TEE, FL
	TEE, MJ
	TEE, MJxFL
	TEE, FLxMJ
	CROSS, FL
	CROSS, MJ

SURVEY SYMBOLS


	BRASS SURFACE MONUMENT
	NAIL IN CONCRETE
	REBAR & CAP

ABBREVIATIONS	DESCRIPTION
AL	=ALIGNMENT
ANC	=UTILITY POLE ANCHOR
APPROX	=APPROXIMATE
ASPH or AC	=ASPHALT
ASS'Y	=ASSEMBLY
ASTM	=AMERICAN SOCIETY FOR TESTING & MATERIALS
BLDG	=BUILDING
BMP	=BEST MANAGEMENT PRACTICE
BVCS	=BEGIN VERTICAL CURVE STATION
BVCE	=BEGIN VERTICAL CURVE ELEVATION
CB	=CATCH BASIN
CK	=CHECK VALVE
C/L	=CENTERLINE
CESCL	=CERTIFIED EROSION SEDIMENT CONTROL LEAD
COL	=COLUMN
CMP	=CORRUGATED METAL PIPE
C.O.	=CLEAN OUT
CONC. C	=CONCRETE
COR	=CORNER
CPP	=CORRUGATED POLYETHYLENE PIPE
CSTC	=CRUSHED SURFACING TOP COURSE
DDCVA	=DOUBLE DETECTOR CHECK VALVE ASSEMBLY
DF	=DRAIN FIELD
DI	=DUCTILE IRON
DO	=DISSOLVED OXYGEN
DR	=DIAMETER RATIO
DS	=DOWNSPOUT
EB	=EXPLORATION BORING
EFFL	=EFFLUENT
EG	=EXISTING GRADE
ELEV. EL	=ELEVATION
EOG	=EDGE OF GRAVEL
EOP	=EDGE OF PAVEMENT
EP	=EXPLORATION PIT
EXIST. EX	=EXISTING
EVCS	=END VERTICAL CURVE STATION
EVCE	=END VERTICAL CURVE ELEVATION
FDC	=FIRE DEPARTMENT CONNECTION
FF	=FINISH GRADE
FG	=FINISH GRADE
FL	=FLOWLINE OR FLANGE (CONNECTION)
FLC	=FLOWLINE
FNC	=FLOWLINE OF CURB
GB	=GRADE BREAK
GMET	=GAS METER
GP	=GUY POLE
GPM	=GALLONS PER MINUTE
GRVL. G	=GRAVEL
GUTT	=GUTTER
GV	=GATE VALVE
HB	=HOSE BIB
HDC	=HOT-DIP GALVANIZED
HDPE	=HIGH DENSITY POLYETHYLENE
H-V	=HORIZONTAL-VERTICAL
HWL	=HIGH WATER LEVEL
HYD	=HYDRANT
IE	=INVERT ELEVATION
INV	=INVERT
LF	=LINEAR FEET
LUM	=LUMINAIRE
LT	=LEFT
MAX	=MAXIMUM
MB	=MAIL BOX
MBR	=MEMBRANE BIO-REACTOR
MC	=MAINTENANCE CLEANING
MFEM	=MEMBRANE FILTRATION EQUIPMENT
MFR	=MANUFACTURER
MH	=MANHOLE
MIN	=MINIMUM
MISC	=MISCELLANEOUS
MJ	=MECHANICAL JOINT
MLSS	=MIXED LIQUOR SUSPENDED SOLIDS
MW	=MONITORING WELL
NPDES	=NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM
O.C.	=ON CENTER
O.C.E.W	=ON CENTER EACH WAY
OD	=OUTSIDE DIAMETER
OHP	=OVERHEAD POWER
OHT	=OVERHEAD TELEPHONE
OSHA	=OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
PC	=POINT OF CURVATURE
PCC	=POINT OF CONTINUING CURVATURE
PV	=POST INDICATOR VALVE
P/L	=PROPERTY LINE
PLC	=PROGRAMMABLE LOGIC CONTROLLER
PLTR	=PLANTER
POI	=POINT ON LINE
PROP	=PROPOSED
PS	=PUMP STATION
PSI	=POUNDS PER SQUARE INCH
PT	=POINT OF TANGENCY
PVC	=POLYVINYL CHLORIDE
PVI	=POINT OF VERTICAL INTERSECTION
PW	=POTABLE WATER
R	=RADIUS
RCK	=ROCK/BOULDER
RET	=RETAINING
REC	=RECORD
REQ'D	=REQUIRED
RI	=RAPID INFILTRATION
RPBA	=REUSE PRESSURE BACKFLOW ASSEMBLY
RR	=RAILROAD
RT	=RIGHT
R/W or ROW	=RIGHT-OF-WAY
RW	=REUSE WATER
SCADA	=SUPERVISORY CONTROL AND DATA ACQUISITION
SCH	=SCHEDULE
SDCB	=STORM DRAIN CATCH BASIN
SD	=STORM DRAIN
SDMH	=STORM DRAIN MANHOLE
SFH	=SINGLE FAMILY HOUSING
SH	=SHRUB/BUSH



805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9061

www.wilsonengineering.com



DESIGNED BY	JGC
DRAWN BY	CJP
CHECKED BY	AWL

CITY OF FERNDALE

WACOM COUNTY

WASHINGTON

PUMP STATION NO. 4


EXISTING SITE PLAN

& FUEL TANK DEMOLITION INFORMATION


DATE	4/22/2015
SCALE	AS SHOWN
JOB NUMBER	2013-037

C2.1
OF
23

BID SET



W:\2013\2013-037 Ferndale PS No 4 Upgrade\Drawings\2-C2.2-C2.3 PROPOSED SITE PLANS.dwg, 6/12/2015 11:29:55 AM, cjp



PROPOSED SURFACING ELEVATIONS


x ①	23.25
x ②	23.25
x ③	23.40
x ④	23.25
x ⑤	23.50
x ⑥	23.50
x ⑦	23.60
x ⑧	23.50
x ⑨	23.60
x ⑩	23.50
x ⑪	23.75
x ⑫	23.65
x ⑬	23.75
x ⑭	23.50
x ⑮	23.25
x ⑯	23.50

PROPOSED SURFACING LEGEND

- = PROPOSED ASPHALT PAVEMENT PER DETAIL A ON SHEET C4.2
- = PROPOSED CRUSHED SURFACING PER DETAIL B ON SHEET C4.2
- = EXISTING CRUSHED SURFACING RESTORE TO ORIGINAL CONDITION AFTER CONSTRUCTION COMPLETION

BID SET

WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9061
www.wilsonengineering.com



DESIGNED BY JCC
DRAWN BY CJP
CHECKED BY AVL

CITY OF FERNDALE

WHATCOM COUNTY WASHINGTON

PUMP STATION NO. 4

PROPOSED SITE GRADING AND DRAINAGE


DATE 4/22/2015
SCALE AS SHOWN
JOB NUMBER 2013-037

SHEET C2.3

OF

23

W:\2013\2013-037 Ferndale PS No 4 Upgrade\Drawg\C2.4 TESC.dwg, 6/12/2015 10:43:43 AM, cjp



TESC PLAN

NARRATIVE

EROSION AND SEDIMENT CONTROL BMPs: ANTICIPATED BMPs THAT WILL BE UTILIZED INCLUDE: MINIMIZING VEGETATION REMOVAL, TEMPORARY COVER MEASURES, PERMANENT SEEDING & PLANTING, SURFACE ROUGHING, AND FILTER FENCING. OTHER BMPs MAY BE UTILIZED TO MINIMIZE EROSION AND SEDIMENT TRANSPORT AS CONSTRUCTION SCHEDULES AND WEATHER CONDITIONS DICTATE.

TEMPORARY STABILIZATION: ALL DISTURBED AREAS SHALL BE STABILIZED IF IN THE EVENT OF RAIN. ALL DISTURBED AREAS SHALL BE STABILIZED IF UNWORKED FOR SEVEN DAYS.

PERMANENT STABILIZATION: ALL DISTURBED AREAS OUTSIDE OF ROADWAY SHOULDERS AND PARKING AREAS WILL BE PERMANENTLY LANDSCAPED OR SEEDED AND RESTORED TO THEIR EXISTING CONDITIONS.

CONVEYANCE BYPASS: PROVISION FOR BYPASS OF STORMWATER CONVEYANCE SHALL BE PROVIDED. BYPASS SHALL BE INSTALLED FOR THE DURATION OF THE WORK. MATERIALS FOR BYPASS NEED NOT BE INSTALLED WHILE WORK IS IN PROGRESS AT A PARTICULAR LOCATION, BUT MATERIALS AND EQUIPMENT FOR IMMEDIATE INSTALLATION SHALL BE ON HAND. BYPASS SHALL BE IN PLACE WHILE SITE IS UNATTENDED FOR GREATER THAN 12 HOURS. A TRENCH MAY BE DUG FOR THE BYPASS PRIOR TO INSTALLATION OF BYPASS IF NECESSARY AND FEASIBLE. ANY PIPING USED FOR BYPASS SHALL BE OF A DIAMETER AT LEAST 3/4 OF THE EXISTING PIPE/CULVERT DIAMETER.

MAINTENANCE: THE BMPs SHALL BE INSPECTED AS NEEDED (MINIMUM OF ONCE EVERY THREE DAYS) AND DURING/AFTER RAINFALL EVENTS. THE BMPs WILL BE MAINTAINED UNTIL THE RISK OF EROSION HAS PASSED AND THE AREA IS PERMANENTLY STABILIZED.

GENERAL NOTES

1. BMPs: BEST MANAGEMENT PRACTICES (BMPs) REFERRED TO ON THIS PLAN AND IN THESE NOTES SHALL BE CONSTRUCTED AND MAINTAINED AS DESCRIBED IN DEPARTMENT OF ECOLOGY'S STORMWATER MANAGEMENT MANUAL FOR THE PUGET SOUND BASIN, CHAPTER II-5, "STANDARDS AND SPECIFICATIONS FOR BEST MANAGEMENT PRACTICES FOR EROSION AND SEDIMENT CONTROL."
2. EXTENT: THE EXTENT OF EROSION AND SEDIMENTATION CONTROL MEASURES IS DEPENDENT ON WEATHER CONDITIONS, SITE SLOPES, LENGTH OF TIME GROUND IS LEFT EXPOSED, AND THE AREA OF EXPOSED GROUND. THE CONTRACTOR SHALL AT ALL TIMES MINIMIZE THE RISK OF SITE EROSION BY CAREFUL SCHEDULING AND BY IMPLEMENTING AND MAINTAINING BMPs UNTIL THE SITE IS PERMANENTLY STABILIZED.
3. UNWORKED SOILS: ALL EXPOSED AND UNWORKED SOILS SHALL BE STABILIZED BY SUITABLE AND TIMELY APPLICATION OF BMPs.
4. VEGETATION: EXISTING VEGETATION SHALL BE PRESERVED WHERE ATTAINABLE.
5. SLOPES: CUT AND FILL SLOPES SHALL BE CONSTRUCTED IN A MANNER THAT WILL MINIMIZE EROSION. SLOPES SHALL BE STABILIZED AS SOON AS POSSIBLE.
6. OUTLETS: STABILIZATION ADEQUATE TO PREVENT EROSION OF OUTLETS AND ADJACENT STREAM BANKS SHALL BE PROVIDED AT THE OUTLETS OF ALL CONVEYANCE SYSTEMS.
7. INLETS: ALL EXISTING AND PROPOSED STORM DRAIN INLETS SHALL BE PROPERLY MAINTAINED AND PROTECTED FROM SILTATION.
8. ENTRANCES: PROVISION SHALL BE MADE TO MINIMIZE THE TRANSPORT OF SOIL ONTO THE PAVED ROAD. IF SOIL IS TRANSPORTED ONTO A ROAD SURFACE, THE ROADS ADJACENT TO THE CONSTRUCTION SITE SHALL BE CLEANED ON A WEEKLY BASIS. STREET WASHING SHALL BE ALLOWED ONLY IF WASHWATER IS INFILTRATED IN THE RIGHT OF WAY.
9. TEMPORARY CONSTRUCTION ENTRANCE: IN PLACE OF A CONSTRUCTED CONSTRUCTION ENTRANCE, CONTRACTOR SHALL PROVIDE ADEQUATE PROVISIONS TO ENSURE THAT NO SEDIMENT IS TRACKED OFF THE CONSTRUCTION SITE. IN THE EVENT THAT SEDIMENT TRACKING OCCURS, CONTRACTOR SHALL REMOVE ALL TRACKED SEDIMENT IMMEDIATELY.
10. SITE RUNOFF: PRIOR TO FLOWING OFF THE SITE, STORMWATER RUNOFF SHALL PASS THROUGH A SILT FENCE OR EQUAL BMP.
11. ADJACENT PROPERTIES: PROPERTIES ADJACENT TO THE PROJECT SHALL BE PROTECTED FROM SEDIMENT DEPOSITION.
12. DOWNSTREAM WATERWAYS & PROPERTY: PROPERTIES AND WATERWAYS DOWNSTREAM FROM THE CONSTRUCTION SITE SHALL BE PROTECTED FROM EROSION DUE TO ANY TEMPORARY CHANGES IN VOLUME, VELOCITY, AND PEAK FLOW OF STORMWATER RUNOFF FROM THE PROJECT SITE.
13. REMOVAL OF BMPs: ALL TEMPORARY EROSION AND SEDIMENT CONTROL BMPs SHALL BE REMOVED WITHIN 30 DAYS AFTER FINAL SITE STABILIZATION IS ACHIEVED OR AFTER THE TEMPORARY BMPs ARE NO LONGER NEEDED. TRAPPED SEDIMENT SHALL BE REMOVED OR STABILIZED ON-SITE. DISTURBED SOIL AREAS RESULTING FROM REMOVAL SHALL BE PERMANENTLY STABILIZED.
14. INSPECTIONS: ALL BMPs SHALL BE INSPECTED, MAINTAINED, AND REPAIRED BY THE CONTRACTOR AS NEEDED TO ASSURE CONTINUED PERFORMANCE OF THEIR INTENDED FUNCTION. ALL ON-SITE EROSION AND SEDIMENT CONTROL MEASURES SHALL BE INSPECTED REGULARLY AS NEEDED (AT LEAST ONCE EVERY SEVEN DAYS) AND DURING/WITHIN 24 HOURS AFTER ANY STORM EVENT OF GREATER THAN 0.5-INCHES OF RAIN PER 24-HOUR PERIOD.
15. REPORTS: THE CONTRACTOR SHALL PREPARE AND MAINTAIN REPORTS SUMMARIZING THE SCOPE OF INSPECTIONS, THE PERSONNEL CONDUCTING THE INSPECTION, THE DATES OF THE INSPECTION, MAJOR OBSERVATIONS ACTIONS TAKEN AS A RESULT OF THESE INSPECTIONS.
16. OTHER REQUIREMENTS: THE ENGINEER, OWNER, CITY OF FERNDAL, DEPARTMENT OF ECOLOGY, OR OTHER AGENCIES MAY REQUIRE BMPs IN ADDITION TO WHAT IS SHOWN ON THIS PLAN IF NECESSARY TO PREVENT VIOLATIONS OF SURFACE WATER QUALITY. THE CONTRACTOR SHALL IMPLEMENT THE BMPs AS REQUIRED.
17. IF AREA OF DISTURBANCE WILL EXCEED 1.0 ACRES, CONTRACTOR SHALL COMPLY WITH NPDES CONSTRUCTION GENERAL PERMIT REQUIREMENTS INCLUDING, BUT NOT LIMITED TO: FILING OF N.O.I. PUBLIC NOTICE, PREPARATION AND MAINTENANCE OF A SWPPP, MONITORING, REPORTING AND FILING OF A N.O.T.

LEGEND

— SF — = SILT FENCE BMP C-233

BMP C233 – SILT (FILTER FABRIC) FENCE


PURPOSE: USE OF A SILT FENCE REDUCES THE TRANSPORT OF COARSE SEDIMENT FROM A CONSTRUCTION SITE BY PROVIDING A TEMPORARY PHYSICAL BARRIER TO SEDIMENT AND REDUCING THE RUNOFF VELOCITIES OF OVERLAND FLOW.

INSTALLATION: USE DOWN SLOPE OF DISTURBED AREAS AS SHOWN ON THE PLAN AND AS NEEDED TO RESPOND TO SITE SPECIFIC CONDITIONS. GEOTEXTILE SHALL MEET THE FOLLOWING STANDARDS: POLYMETRIC MESH AOS (ASTM D4751) = 0.60 MM MAXIMUM FOR SLIT FILM WOVENS, 0.30 MM MAXIMUM FOR ALL OTHER GEOTEXTILES TYPES, AND 0.15 MM FOR ALL FABRIC TYPES, WATER PERMITTIVITY (ASTM D4491) = 0.2 SEC(-1) MINIMUM, GRAB TENSILE STRENGTH (ASTM D4632) = 180 POUNDS MINIMUM FOR EXTRA STRENGTH FABRIC, 100 POUNDS MINIMUM FOR STANDARD STRENGTH FABRIC, GRAB TENSILE ELONGATION (ASTM D4632) = 30% MAXIMUM, ULTRAVIOLET RESISTANCE (ASTM D4355) = 70% MINIMUM.

STANDARD STRENGTH FABRICS SHALL BE SUPPORTED WITH WIRE MESH, CHICKEN WIRE, 2-INCH X 2-INCH WIRE, SAFETY FENCE, OR JUTE MESH TO INCREASE THE STRENGTH OF THE FABRIC. SILT FENCE MATERIALS ARE AVAILABLE THAT HAVE SYNTHETIC MESH BACKING ATTACHED.

THE MINIMUM HEIGHT OF THE TOP OF THE SILT FENCE SHALL BE 2 FEET AND THE MAXIMUM HEIGHT SHALL BE 2.5 FEET.

MAINTENANCE: INSPECT THE FENCE AFTER RAINFALL EVENTS FOR SEDIMENT DEPOSITS UPSTREAM OF THE FENCE. REMOVE SEDIMENT DEPOSITS WHEN THEY REACH A DEPTH OF APPROXIMATELY 8 INCHES DEEP. REPLACE FILTER FABRIC FENCES DAMAGED BY CONSTRUCTION EQUIPMENT OR ULTRAVIOLET BREAKDOWN.



BMP C-233
SILT FENCE
NOT TO SCALE

IN PLACE OF A CONSTRUCTED CONSTRUCTION ENTRANCE, CONTRACTOR SHALL PROVIDE ADEQUATE PROVISIONS TO ENSURE THAT NO SEDIMENT IS TRACKED OFF THE CONSTRUCTION SITE. IN THE EVENT THAT SEDIMENT TRACKING OCCURS, CONTRACTOR SHALL REMOVE ALL TRACKED SEDIMENT IMMEDIATELY.

WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9061
www.wilsonengineering.com




DESIGNED BY	JCC
DRAWN BY	CJP
CHECKED BY	AWL

CITY OF FERNDAL	WASHINGTON
WHATCOM COUNTY	PUMP STATION NO. 4
	TESC PLAN, DETAILS & NOTES

SHEET	DATE	SCALE	JOB NUMBER
C2.4	4/22/2015	AS SHOWN	2013-037
OF			23

BID SET

W:\2013\2013-037 Ferndale PS No 4 Upgrade\DWG\C3.1-3.2-Plan and Profile.dwg, 6/12/2015 10:04:20 AM, cjp



BID SET






Wilson
SURVEY/ENGINEERING
WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9061
www.wilsonengineering.com

CITY OF FERNDALE
PUMP STATION NO. 4
EXISTING PLAN AND PROFILE LAYOUT

SHEET	DATE	SCALE	JOB NUMBER
C3.1	4/22/2015	AS SHOWN	2013-037
OF			23

A diagram of a rectangle. The vertical side on the left is labeled with the number 25. The horizontal side at the bottom is labeled with the number 20.




A horizontal scale bar with a black and white checkered pattern on the left and a solid black pattern on the right. The word 'SCALE' is written below the left end, and 'FEET' is written below the right end. Numerical markings are placed above the bar at positions 2, 0, 2, and 4.


BID SET

- ① 8" D.I. SPOOL, FxMJ
- ② 8" D.I. SPOOL, FxF
- ③ 8" D.I. 90° BEND, FxF
- ④ NOT USED
- ⑤ 8" CHECK VALVE, FxF
- ⑥ 8" GATE VALVE, FxF
- ⑦ 8" D.I. 22½° BEND, FLxFL
- ⑧ 8" D.I. 45° BEND, FLxFL
- ⑨ 8" BOLTED FLEX COUPLING,
ROMAC STYLE "501" OR EQUAL.
- ⑩ 8" ROMAC STYLE "611" PIPE RESTRAINING SYSTEM
OR EQUAL (200 PSI MINIMUM RESTRAINT)
- ⑪ 8" FLANGED COUPLING ADAPTOR (RESTRAINED)
- ⑫ 8" D.I. PIPE, FORCE MAIN, MJ
- ⑬ PRESSURE GAGE, ISOLATOR, & SHUTOFF VALVE
- ⑭ ADJUSTABLE PIPE SUPPORTS (6 TOTAL)
- ⑮ 8"x6" D.I. REDUCER (NOMINAL) FOR PUMP
DISCHARGE, FxF. CONFIRM SIZE WITH PUMP MFR.
- ⑯ 8" TRUE WYE
- ⑰ 8" ELECTROMAGNETIC FLOW METER
- ⑱ 4" FLAP GATE FOR DRAIN PIPE.


W:\2013\2013-037 Ferndale PS No 4 Upgrade\Drawg\C4.1-Details.dwg, 6/12/2015 10:11:13 AM, cjp




A
*
VERTICAL PIPE BRACE
NOT TO SCALE




B
*
FLOOR/WALL SLEEVE DETAIL
NOT USED



C
*
PIPE SUPPORT DETAIL




1. 6-IN. STAINLESS STEEL FEMALE CAM & GROOVE BY 6-IN. FNPT ADAPTER
2. 6-IN. STAINLESS STEEL NPT NIPPLE (MIN. 8" LONG)
3. 6-IN. D.I. FLANGE TO 6-IN. FNPT ADAPTER (COMPANION FLANGE)
4. 6-IN. D.I. LONG RADIUS BEND (FL)
5. 6-IN. GATE VALVE (FL)
6. D.I. TEE (FL) - SEE NOTE 4
7. 8-IN. GATE VALVE (FLXMJ) - SEE NOTE 4
8. CAST IRON VALVE BOX
9. H2O LOADING CONCRETE METER BOX WITH CAST ITON LID. LID TO BE LOCKABLE WITH PAD LOCK



- NOTES:**
1. INSTALL ADDITIONAL PIPING BETWEEN TEE AND PUMPING PORT VALVE AS REQUIRED TO INSTALL PORT IN LOCATION APPROVED BY ENGINEER.
 2. BACKFILL IN AND AROUND METER BOX SHALL BE CRUSHED SURFACING TOP COURSE PER WSDOT 9-03.9(3). INSTALL MINIMUM 1 FOOT WIDE GRAVEL 'COLLAR' AROUND BOX.
 3. ALLOW 4-IN. SPACE BETWEEN THE TOP OF THE CAM & GROOVE FITTING AND THE INSIDE OF THE METER BOX LID.
 4. FORCE MAIN IS 8-IN. D.I. SNORKEL WILL REQUIRE AN 8x6 TEE AND TWO 8-IN. GATE VALVES (FLXMJ).

D
*
BYPASS PUMPING PORT ASSEMBLY
NOT TO SCALE



BID SET



DESIGNED BY JCC
DRAWN BY CJP
CHECKED BY AVL

CITY OF FERNDALE
WHATCOM COUNTY
WASHINGTON
PUMP STATION NO. 4
DETAILS

DATE 4/22/2015
SCALE AS SHOWN
JOB NUMBER 2013-037




SHEET C4.1
OF 23

Wilson
SURVEY/ENGINEERING

WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9661
www.wilsonengineering.com


W:\2013\2013-037 Ferndale PS No 4 Upgrade\Drawg\C4.1-Details.dwg, 6/12/2015 10:12:37 AM, cjp

1



SIZING TABLE				
PIPE DIA	T (min)	H (min)	SHACKLE RODS	REINFORCING
6"	18"	36"	(4) 5/8" dia	#4 @ 10" OC EW
8"	18"	42"	(4) 3/4" dia	#4 @ 12" OC EW
10"	24"	52"	(6) 3/4" dia	#4 @ 12" OC EW
12"	24"	54"	(6) 7/8" or (8) 3/4" dia	#4 @ 8" OC EW
14"	24"	56"	(8) 7/8" or (10) 3/4" dia	#4 @ 6" OC EW
16"	30"	58"	(10) 7/8" dia	#4 @ 5" OC EW

BLOCK SIZES GOOD TO MAXIMUM 300psi TEST PRESSURE



- NOTES
1. THIS STANDARD DETAIL IS FOR DEADMAN BLOCKING ONLY.
 2. CONCRETE BLOCK SHALL BE PER APWA SPECIFICATION 7-11.3(13), CURRENT EDITION.
 3. MAINTAIN 18" MINIMUM COVER OVER THE TOP OF BLOCK.
 4. BOTTOM OF BLOCK IS TO BE ON UNDISTURBED SOIL.
 5. TRENCH TO BE BACKFILLED WITH CRUSHED ROCK COMPACTED TO FIRM AND UNYIELDING CONDITION ON ALL SIDES OF BLOCK AND A DISTANCE OF 4' MIN. IN FRONT OF BLOCK TO FULL DEPTH OF BLOCK.
 6. UPON EXTENSION OF WATER MAIN, SHACKLE RODS ARE TO BE CUT, REMOVE PLUG. CONCRETE BLOCK TO REMAIN IN PLACE.
 7. FOR SOIL CONDITIONS NOT SHOWN, BLOCK IS TO BE DESIGNED BY ENGINEER.
 8. IF BLOCK CANNOT BE KEYED INTO UNDISTURBED SOIL TO THE SATISFACTION OF THE DISTRICT ENGINEER, a) THE BLOCK LENGTH SHALL BE EXTENDED TO PROVIDE AN ADEQUATE KEY OR b) CDF SHALL BE USED TO FILL BACK TO NATIVE SOIL OR c) THE TRENCH SHALL BE BACKFILLED AND COMPACTED TO FIRM AND UNYIELDING CONDITION A MINIMUM DISTANCE OF 15 FEET IN FRONT OF THE BLOCK TO THE SATISFACTION OF THE DISTRICT ENGINEER.
 9. SEE STANDARD DETAIL W-07 FOR ADDITIONAL SHACKLE ROD INFORMATION.

MIN. BLOCK LENGTH (L)						
SOIL CONDITION						
PIPE Ø	SOFT CLAY	SILT	SANDY SILT	SAND	SANDY CLAY	HARD CLAY
6"	84"	72"	72"	72"	72"	72"
8"	108"	84"	75"	75"	75"	75"
10"	132"	104"	77"	77"	77"	77"
12"	180"	138"	82"	80"	80"	80"
14"	228"	174"	102"	82"	82"	82"
16"	288"	216"	126"	100"	84"	84"

2


REVERSE THRUST BLOCK DETAIL

NOT TO SCALE

BID SET

NO.	REVISIONS	BY	DATE
1	REVISION PER ADDENDA	JGC	6/5/15

WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9061
www.wilsonengineering.com




DESIGNED BY JGC
DRAWN BY CJP
CHECKED BY CJP

CITY OF FERNDALE
WHATCOM COUNTY
WASHINGTON
PUMP STATION NO. 4 ADDENDUM No.1
WATER MAIN CONNECTION DETAILS

DATE 4/22/2015
SCALE AS SHOWN
JOB NUMBER 2013-037

SHEET C4.1A
OF 23


W:\2013\2013-037 Ferndale PS No 4 Upgrade\Drawg\C4.1-Details.dwg, 6/12/2015 10:14:00 AM, cjp



STANDARD ASPHALT SECTION

**TYPICAL ASPHALT
CONCRETE PAVEMENT SECTION**


A
*
NOT TO SCALE




COMPACTED SUBGRADE:
SUITABLE NATIVE OR COMMON
BORROW MIN 95% OPTIMUM
DENSITY COMPACTION (ASTM
D1557).

TYPICAL GRAVEL ACCESS SECTION

B
*
NOT TO SCALE



THRUST BLOCK TABLE						
MINIMUM BEARING AREA AGAINST UNDISTURBED SOIL IN SQUARE FEET						
PIPE SIZE	A	B	C	D	E	
4"	2	2	2	2	2	
6"	4	3	2	2	2	
8"	7	5	4	2	2	
10"	11	8	6	3	2	
12"	16	12	9	5	3	
16"	29	20	16	8	4	
20"	45	32	24	13	6	




- NOTES**
1. SQUARE FEET OF CONCRETE THRUST BLOCK AREA IS BASED ON 200 P.S.I. INTERNAL PRESSURE, A SOIL SAFE BEARING OF 3000 POUNDS PER SQUARE FOOT AND A FACTOR OF SAFETY OF 1.5.
 2. BEARING AREA MUST BE ADJUSTED FOR INTERNAL PRESSURES AND LOWER SOIL BEARING VALUES.
 3. CONCRETE BLOCKING SHALL BE CAST IN PLACE AND HAVE A MINIMUM OF 1/4 SQUARE FOOT BEARING AGAINST THE FITTING.
 4. BLOCK SHALL BEAR AGAINST FITTINGS ONLY AND SHALL BE CLEAR OF JOINTS TO PERMIT TAKING UP OR DISMANTLING JOINT.

5. THE CONTRACTOR SHALL INSTALL BLOCKING WHICH IS ADEQUATE TO WITHSTAND FULL TEST PRESSURE AS WELL AS TO CONTINUOUSLY WITHSTAND OPERATING PRESSURE UNDER ALL CONDITIONS OF SERVICE.
6. STAINLESS STEEL BANDING SHALL BE USED AT 2" PVC VERTICAL BENDS INSTEAD OF 1" RODS. CONTACT ENGINEER FOR SIZING OF THRUST BLOCK AND DETAILS.
7. ALL BENDS, TEES & CROSSES SHALL INCLUDE RESTRAINED JOINTS (ROMAC GRIPPER) AS WELL AS THRUST BLOCKING.

WATERLINE AND FORCEMAIN THRUST BLOCKING SCHEDULE

C
*
NOT TO SCALE



UNPAVED AREAS

PAVED AREAS

FLEXIBLE PIPE NOTES:

- 1) PROVIDE UNIFORM SUPPORT UNDER BARRELS.
- 2) HAND TAMP UNDER HAUNCHES.
- 3) COMPACT BEDDING MATERIAL TO 95% MAX. DENSITY; DIRECTLY OVER PIPE, HAND TAMP ONLY.
- 4) SEE "EXCAVATION AND PREPARATION OF TRENCH" IN SANITARY SEWERS SECTION OF THE STANDARD WSDOT/APWA SPECIFICATIONS FOR TRENCH WIDTH "W" AND TRENCHING OPTIONS. THE PIPE ZONE WILL BE THE ACTUAL TRENCH WIDTH. THE MINIMUM CONCRETE WIDTH SHALL BE 1-1/2 I.D. + 18".
- 5) ROCKS OR LUMPS LARGER THAN 1" PER FOOT OF PIPE DIAMETER SHALL NOT BE USED IN THE BACKFILL MATERIAL.
- 6) SEE "BEDDING MATERIAL FOR FLEXIBLE PIPE" IN AGGREGATES SECTION OF THE WSDOT/APWA STANDARD SPECIFICATIONS FOR THE MATERIAL SPECIFICATIONS.

TYPICAL PIPE TRENCHING & BACKFILL

D
*
NOT TO SCALE

BID SET



DESIGNED BY JCC
DRAWN BY CJP
CHECKED BY AVL

CITY OF FERNDALE
PUMP STATION NO. 4
DETAILS


DATE 4/22/2015
SCALE AS SHOWN
JOB NUMBER 2013-037

SHEET C4.2
OF 23

Wilson
SURVEY/ENGINEERING

WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9061
www.wilsonengineering.com

W:\2013\2013-037 Ferndale PS No 4 Upgrade\Drawg\S4.0 TYPICAL DETAILS.dwg, 4/22/2015 9:09:35 AM, JGS



NOTES:
1. PLACE SLAB ON FIRM BEARING MATERIAL.
2. OMIT VAPOR BARRIER AT SIMILAR OUTDOOR SLABS.

A
S4.0

Concrete Pad for Generator

Scale: N.T.S.

STRUCTURAL NOTES

BUILDING CODE CRITERIA

- All construction is to be in accordance with the minimum provisions of the 2009 International Building Code (IBC). Where these plans and specifications do not state specifically otherwise the provisions of the UBC shall apply.
- These drawings show the design of a foundation for a pre-manufactured metal building, as well as basic design criteria for which the metal building shall be designed. Wilson Engineering is not responsible for the design of the metal building. The manufacturer shall have on staff or retain a Professional Engineer for the design of the building itself. The design shall be based on the loads given below.
- Design Roof (Snow) Load: 25 PSF
- Lateral Loads:

Seismic Loading	Wind Loading (3 s gust)
Site Class D	Basic Wind Speed 90 MPH
S ds 1.14	Exposure C
S d1 0.33	Kzt (ASCE 7-10) 1.1
Importance Factor	1.5
- Special Inspections
No Special Inspections are required for this project. Footing concrete requires $f_c \leq 2500$ psi for structure; higher strengths have been specified for other reasons. Special inspection is not required.
- Structural Observation
The Structural Engineer of record will perform Structural Observations as defined by the IBC, if required.

01000 GENERAL

- Employ good standards of workmanship throughout. Provide all materials and perform all construction as indicated. Secure architect's approval for substitutions.
- See specifications for detailed material and methods. In case of conflict between applicable codes, these notes, and the drawings, the more stringent will govern.
- Verify all dimensions in the field, and upon discovery of any discrepancies between the drawings and/or field conditions notify Wilson Engineering.
- Use these drawings in conjunction with the architectural and other drawings. They are not to stand alone. These drawings and the designs herein are copyrighted by Wilson Engineering, and are for use on this project only. They may not be copied or used for any other project or purpose other than as originally intended without written approval from Wilson Engineering.
- Do not scale drawings.
- Use typical details and schedules wherever applicable.
- The drawings do not indicate the method of construction. The contractor is solely responsible for design and supply of all erection bracing and shoring, and for safety programs, methods, and procedures of operation for the construction of the design shown on these drawings.

02220 FOUNDATIONS & EARTHWORK

- Spread footings are designed for a maximum total pressure of 1500 PSF.
- Remove all topsoil and organic material from building area, including exterior slabs and walks attached to building.
- Place footings against firm, undisturbed bearing soil or approved fill, as identified in soils report prepared by GeoTest Services Inc., June 19, 2013.

03150 CONCRETE ACCESSORIES & HARDWARE

- Adhesive-installed anchor bolts shall be steel of a grade appropriate to the application, with epoxy or polymer resin adhesive of consistency appropriate to the application. Anchors shall have a current ICC-ES report stating that they are approved for use in cracked concrete.
Accepted products include:
 - Simpson Strong-Tie IXP anchor with Set-XP adhesive
 - Hilti HAS threaded rods with Hilti HIT-RE 500-SD system adhesive
- Expansion anchor-bolts shall be steel wedge-type bolts, with hold diameter equal to bolt diameter. Dry location bolts shall be cad-plated; bolts in exterior locations and wet locations shall be stainless steel. Anchors shall have a current ICC-ES report stating that they are approved for use in cracked concrete. Accepted products include:
 - Simpson "Strong-Bolt"
 - Hilti "HSL-3"
 - ITW Red Head "Tru-Bolt+" Seismic Wedge

- Expansion or epoxy anchor bolts shall have minimum embedment of 12 bolt diameters, unless noted otherwise on drawings. The hole diameter and preparation shall be per manufacturer's instructions; thoroughly clean holes before installing bolts.
- Cast-in-place anchor bolts set in concrete or masonry shall conform to ASTM F1554-07 Grade 36, with Supplement S1 and shall be either headed steel bolts with rolled or cut threads and a standard washer, or threaded steel rod with a standard nut and washer at the embedded end. Do not use "J" bolts without nuts and washer at the embedded end.
- Embedment (to the closest face of the washer) for cast-in-place anchors shall not be less than 7 inches.
- For further information regarding anchors at building column base plates, consult the metal building manufacturer.

03300 REINFORCED CONCRETE

- Reinforcing shall be ASTM A615, Gr. 60, except that #3 bars may be Gr. 40. Welded Wire Fabric: Do not use WWF in slabs, use rebar per details.
- Bar detailing not shown otherwise, and support of reinforcing bars shall conform to the CRSI Manual of Standard Practice. Reinforcing which is marked "continuous" shall extend as far as possible in the concrete and terminate in a 12-diameter bend or per typical corner details, as appropriate. Shop fabricate all bends. Lap all continuous bars 48 dia., wire tie all lap splices. Welding of reinforcing is not permitted.
- Concrete Materials:
Stone aggregate per ASTM C33, ASTM C150 Type I or II Cement
Use ASTM C260 air entraining admixture for outdoor exposure conditions
Water-reducing ASTM C494 Type A is permitted
All concrete shall be ready-mix. Comply with requirements of ASTM C 94.
Concrete 28 day strengths and other properties shall be as follows:

Applications	f_c (max)	w/c (max)	aggregate Content	Air (psi)
Slabs and Footings	3500	0.45	3/4"	6.0 % \pm 1.5 %
- Hold all bolts, anchors, dowels, reinforcing bars and metal inserts firmly and accurately in place before concrete is poured; do not insert ("stab") after pouring concrete.
- See architectural drawings for all slab finish details, exact location of depressed slab areas, threshold requirements, floor drains, and slopes.
Walkways and sidewalks are not shown on the structural drawings; see architectural drawings for locations, dimensions, finishes, and elevations. Reinforce per typical details, these drawings.

BID SET

WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9061
www.wilsonengineering.com

Wilson
SURVEY / ENGINEERING



DESIGNED BY
CBW
DRAWN BY
SJW
CHECKED BY
JCC



CITY OF FERNDALE
WHATCOM COUNTY
WASHINGTON
PUMP STATION NO. 4
TYPICAL DETAILS

DATE
4/22/2015
SCALE
AS SHOWN
JOB NUMBER
2013-037

SHEET
S1.1
OF
22

RACEWAYS AND CONDUCTORS		CALLOUTS AND DESIGNATIONS		CONTROLS AND INSTRUMENTATION		STANDARD ABBREVIATIONS		PROJECT GENERAL NOTES:	
<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><</div></div></div>									

WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9061
www.wilsonengineering.com




DESIGNED BY BZ
DRAWN BY GH
CHECKED BY BZ

CITY OF FERNDALE, WA
WASHINGTON
WHATCOM COUNTY
PUMP STATION No. 4
ELECTRICAL SYMBOLS AND ABBREVIATIONS


DATE 4/20/2015
SCALE AS SHOWN
JOB NUMBER 2013-037
SHEET E1
OF E11

ELECTRICAL DEMOLITION NOTES:

1. PROVIDE COMPLETE DEMOLITION OF ALL EXISTING EQUIPMENT INCLUDING WET WELL PUMPING SYSTEM, PUMP CONTROL PANEL, INSTRUMENTATION, CONDUIT AND WIRING.
2. RETURN ALL DEMO EQUIPMENT TO OWNER. LEGALLY DISPOSE OF ALL DEMO MATERIALS NOT WANTED BY OWNER.
3. COORDINATE WITH OWNER TO MAINTAIN OPERATIONS DURING CONSTRUCTION PERIOD. SEE CIVIL SPECIFICATIONS.




ELECTRICAL DEMO PLAN
SCALE: 1" = 5' AT FULL SCALE



DEMO NOTES:

1. PROVIDE COMPLETE ELECTRICAL DEMOLITION OF EXISTING GENERATOR, DIESEL FUEL TANK, AND AUTOMATIC TRANSFER SWITCH.
2. PROVIDE COMPLETE DEMOLITION OF EXISTING WET WELL PUMPS AND INSTRUMENTATION.
3. REMOVE EXISTING LEVEL TRANSDUCER. MAINTAIN AND PROTECT, RETURN TO OWNER FOR FUTURE USE.

1
E2
ELECTRICAL EQUIPMENT DEMO DETAIL
SCALE: NONE



DEMO NOTES:

4. PROVIDE COMPLETE ELECTRICAL DEMOLITION OF EXISTING PUMP CONTROL PANEL AND ELECTRICAL RACEWAY.
5. RELOCATE EXISTING TELEMETRY PANEL TO NEW EQUIPMENT ENCLOSURE. *MAINTAIN PROVIDE NEW TELEMETRY ANTENNA MOUNTING PER DETAIL ON SHEET E5. ON EXISTING POLE. PROVIDE NEW ANTENNA CABLE AND RACEWAY, ROUTE TO NEW TELEMETRY PANEL LOCATION.*
6. DEMO EXISTING METER BASE AND 100 AMP SERVICE DISCONNECT. PROVIDE NEW METER BASE, FUSED DISCONNECT AHEAD OF METER BASE, AND POLE RISER PER PSE REQUIREMENTS. PROVIDE NEW UNDERGROUND SERVICE RACEWAY FROM NEW METER BASE ON POLE TO NEW SERVICE DISCONNECT IN EQUIPMENT ENCLOSURE; SEE SHEETS E3, E5. COORDINATE WITH PUGET SOUND ENERGY FOR ELECTRICAL SERVICE UPGRADE.

2
E2
POWER POLE DEMO DETAIL
SCALE: NONE


BID SET



Z Engineers, PLLC
One Fifth Street, Ste 150
Wenatchee, WA 98801
Tel: 509.888.9364
Fax: 509.888.9365
www.z-engineers.com

NO.	BY	DATE
1	BZ	5/01/15

WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9661
www.wilsonengineering.com




DESIGNED BY	BZ
DRAWN BY	GH
CHECKED BY	BZ

CITY OF FERNDALE, WA
WHATCOM COUNTY
WASHINGTON
PUMP STATION No. 4
ELECTRICAL DEMOLITION

DATE	4/20/2015
SCALE	AS SHOWN
JOB NUMBER	2013-037

SHEET	E2
OF	E11




ELECTRICAL POWER PLAN
SCALE: 1" = 2' AT FULL SCALE

GENERAL NOTES:

- ALL CONDUIT ROUTING IS NOT SHOWN. ELECTRICAL CONTRACTOR SHALL DETERMINE THE BEST ROUTING PATH AND CIRCUIT COMBINATIONS BASED ON FIELD CONDITIONS AND ELECTRICAL CODES.
- CONDUCTOR AND CONDUIT SIZING SHALL BE AS REQUIRED BY NEC.
- EQUIPMENT LOCATIONS AND ARRANGEMENT ARE SCHEMATIC. CONTRACTOR SHALL COORDINATE WITH EQUIPMENT MANUFACTURER FOR DETAILED CONNECTION REQUIREMENTS AND PROVIDE MATERIALS AND INSTALLATION FOR A COMPLETE AND OPERATIONAL SYSTEM.

KEY NOTES:

- PROVIDE RECEPTACLE IN GENERATOR ENCLOSURE FOR BATTERY CHARGER AND BLOCK HEATER.
- OVERSIZE CONDUITS TO WET WELL FOR PUMP CABLES.
- COORDINATE FINAL LOCATION OF AREA LIGHT FIXTURE DURING CONSTRUCTION.




ONE LINE DIAGRAM
SCALE: NONE

LOAD CALCULATION - 480 VAC, 3 PHASE							
EQUIPMENT NO.	DESCRIPTION	KVA/HP	AMPS	DEMAND FACTOR	DEMAND LOAD AMPS	DEMAND FACTOR	GENERATOR LOAD AMPS
P1	PUMP 1 - FLYGT MODEL NP 3202 HT	60 HP	69.0	1.25	86.3	1.25	86.3
P2	PUMP 2 - FLYGT MODEL NP 3202 HT	60 HP	69.0	1.00	69.0	1.00	69.0
LP1	LOAD CENTER	7.5 KVA	15.6	0.65	10.1	0.65	10.1
TOTAL			153.6		165.4		165.4

LOAD CALCULATION
SCALE: NONE

BID SET






INSTRUMENTATION & CONTROL PLAN
SCALE: 1" = 2' AT FULL SCALE

KEY NOTES:

- 1. HAZARDOUS LOCATIONS - WET WELL IS CLASS I, DIV 1 PER NFPA 820, TABLE 4.2, ROW16a. FLOW METER VAULT IS CLASS I, DIV 2 PER NFPA 820, TABLE 4.2, ROW 31a. ALL INSTRUMENTATION, ELECTRICAL EQUIPMENT AND INSTALLATION SHALL BE IN ACCORDANCE WITH NEC ARTICLE 500.
- 2. FIELD COORDINATE HAND HOLE LOCATION. HANDHOLE SHALL BE TRAFFIC RATED AND SIZED PER NEC. SIZE CONDUITS PER NEC TO ACCOMMODATE PUMP AND INSTRUMENTATION CABLES.
- 3. PROVIDE LIMIT SWITCHES FOR EACH GENERATOR DOOR. WIRE LIMIT SWITCHES IN SERIES TO PROVIDE ONE INTRUSION STATUS TO THE TELEMETRY PANEL PLC.

GENERAL NOTES:

- 1. ALL CONDUIT ROUTING IS NOT SHOWN. ELECTRICAL CONTRACTOR SHALL DETERMINE THE BEST ROUTING PATH AND CIRCUIT COMBINATIONS BASED ON FIELD CONDITIONS AND ELECTRICAL CODES.
- 2. EQUIPMENT LOCATIONS AND ARRANGEMENT ARE SCHEMATIC. CONTRACTOR SHALL COORDINATE WITH EQUIPMENT MANUFACTURER FOR DETAILED CONNECTION REQUIREMENTS AND PROVIDE MATERIALS AND INSTALLATION FOR A COMPLETE AND OPERATIONAL SYSTEM.



WET WELL ELEVATION
SCALE: NONE

BID SET




NO.		BY		DATE	
WILSON ENGINEERING, LLC 805 DUPONT STREET BELLINGHAM, WA 98225 (360) 733-6100 • FAX (360) 647-9061 www.wilsonengineering.com					
Wilson SURVEY/ENGINEERING					
DESIGNED BY	BZ	DRAWN BY	CH	CHECKED BY	BZ
CITY OF FERNDALE, WA		WASHINGTON		PUMP STATION No. 4	
WHATCOM COUNTY		INSTRUMENTATION AND CONTROL PLAN		DATE	
4/20/2015		SCALE		AS SHOWN	
SHEET		E4		JOB NUMBER	
OF		E11		2013-037	

1

RADIO ANTENNA MOUNTING INFORMATION:


1. PROVIDE COMPLETE ANTENNA MOUNTING ASSEMBLY INCLUDING A GROUNDED MAST, CONSISTING OF A 2" GALVANIZED RIGID STEEL MAST WITH WEATHERHEAD (SEE DETAIL) SET IN CONCRETE, OR SUPPORTED BY EQUIPMENT SUPPORT STRUCTURES.
2. RELOCATE EXISTING TELEMETRY ANTENNA TO NEW MAST STRUCTURE.
3. ANTENNA ASSEMBLY SHALL INCLUDE A LIGHTNING SURGE ARRESTOR AND CONNECTION TO NEW GROUND ROD AND ELECTRICAL SERVICE GROUNDING ELECTRODE SYSTEM.
4. FIELD COORINATE FINAL ANTENNA MOUNTING HEIGHT AND AIMING. ANTENNA SHALL BE A MAXIMUM OF 20 FEET ABOVE GROUND LEVEL.



ELECTRICAL ENCLOSURE - EXTERIOR ELEVATION
SCALE: NONE

GENERAL NOTES:

1. THESE DRAWINGS SHOW ONLY FUNCTIONAL REQUIREMENTS OF THE ELECTRICAL ENCLOSURE. DETAILED WIRING DIAGRAMS, PANEL SIZING AND LAYOUT SHALL BE PROVIDED BY THE CONTROL PANEL SUPPLIER FOR A COMPLETE AND OPERATIONAL SYSTEM.



ELECTRICAL ENCLOSURE - WIRING DIAGRAM
SCALE: NONE

BID SET



Z Engineers, PLLC
One Fifth Street, Ste 150
Wenatchee, WA 98801
Tel: 509.888.9364
Fax: 509.888.9365
www.z-engineers.com

NO. 1		BY BZ		DATE 5/01/15	
1 BID REVISIONS AS INDICATED					
WILSON ENGINEERING, LLC 805 DUPONT STREET BELLINGHAM, WA 98225 (360) 733-6100 • FAX (360) 647-9661 www.wilsonengineering.com					
DESIGNED BY BZ	DRAWN BY GH	CHECKED BY BZ			
CITY OF FERNDALE, WA			WASHINGTON		
WHATCOM COUNTY			PUMP STATION No. 4		
			ELECTRICAL ENCLOSURE ELEVATION		
DATE 4/20/2015	SCALE AS SHOWN	JOB NUMBER 2013-037			
SHEET E5	OF	E11			


PANEL NAMEPLATE SCHEDULE					
LABEL	ENGRAVING TEXT	LABEL	ENGRAVING TEXT	LABEL	ENGRAVING TEXT
N-1	CITY OF FERDALE PUMP STATION NO.4	N-11	POWER STATUS (WHITE)	N-21	HIGH LEVEL FLOAT (RED)
N-2	PUMP NO.1 HAND OFF AUTO	N-12	PUMP NO.2 HAND OFF AUTO	N-22	LAG START FLOAT (GREEN)
N-3	PUMP NO.1 RUNNING (GREEN)	N-13	PUMP NO.2 RUNNING (GREEN)	N-23	LEAD START FLOAT (GREEN)
N-4	PUMP NO.1 FAIL (RED)	N-14	PUMP NO.2 FAIL (RED)	N-24	PUMP STOP FLOAT (GREEN)
N-5	PUMP NO.1 OVERTEMP (RED)	N-15	PUMP NO.2 OVERTEMP (RED)	N-25	LOW LEVEL FLOAT (RED)
N-6	PUMP NO.1 SEAL FAIL (AMBER)	N-16	PUMP NO.2 SEAL FAIL (AMBER)	N-26	OPERATOR IN TROUBLE (RED)
N-7	PUMP NO.1 RESET	N-17	PUMP NO.2 RESET		
N-8	PUMP CONTROL / FLOAT - PLC	N-18	PUMP NO.2 AMMETER/SELECTOR		
N-9	PUMP NO.1 AMMETER/SELECTOR	N-19	PUMP NO.2 ETM		
N-10	PUMP NO.1 ETM	N-20	---		

KEY NOTES:

- 1
- ALLEN BRADLEY PANELVIEW PLUS 6 700. OPERATOR INTERFACE PROGRAMMING WILL BE PROVIDED BY CITY'S PROGRAMMER, L2 SYSTEMS, UNDER FORCE ACCOUNT. SEE SPECIFICATIONS.
- 2
- FLOW METER FM APPROVED FOR CLASS I, DIV 2 HAZARDOUS AREA.
- 3
- WIRE ALL NEW INSTRUMENTATION TO INTRINSICALLY SAFE AREA IN ELECTRICAL ENCLOSURE AND TO TELEMETRY CONTROL PANEL.
- 4
- PROVIDE POWER DISTRIBUTION, STARTERS FOR DUPLEX PUMP CONTROL SYSTEM. PANEL BUILDER SHALL PROVIDE DETAILED DESIGN BASED ON FUNCTIONAL WIRING DIAGRAMS FOR A COMPLETE AND OPERATIONAL SYSTEM.

GENERAL NOTES:

1.
- THESE DRAWINGS SHOW ONLY FUNCTIONAL REQUIREMENTS OF THE ELECTRICAL ENCLOSURE. DETAILED WIRING DIAGRAMS, PANEL SIZING AND LAYOUT SHALL BE PROVIDED BY THE CONTROL PANEL SUPPLIER FOR A COMPLETE AND OPERATIONAL SYSTEM.



ELECTRICAL ENCLOSURE - ELEVATION
SCALE: NONE

BID SET



WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9061
www.wilsonengineering.com

Wilson
SURVEY/ENGINEERING

DESIGNED BY
BZ

DRAWN BY
GH

CHECKED BY
BZ

CITY OF FERDALE, WA

WASHINGTON

WHATCOM COUNTY

PUMP STATION No. 4

ELECTRICAL ENCLOSURE ELEVATION

DATE
4/20/2015

SCALE
AS SHOWN



JOB NUMBER
2013-037

SHEET
E6

OF
E11


GENERAL NOTES:

1. THESE SCHEMATICS SHOW ONLY FUNCTIONAL REQUIREMENTS OF THE PUMP CONTROL SECTION. DETAILED WIRING DIAGRAMS, PANEL SIZING AND LAYOUT SHALL BE PROVIDED BY THE CONTROL PANEL SUPPLIER FOR A COMPLETE AND OPERATIONAL SYSTEM.
2. ALL INDICATOR LIGHTS ARE NOT SHOWN. PROVIDE WIRING, INTERPOSING RELAYS AS REQUIRED FOR STATUS INDICATOR LIGHTS FOR ALL SIGNALS SHOWN ON SHEET E6.



PUMP CONTROL - WIRING DIAGRAM

SCALE: NONE



INTRINSICALLY SAFE FLOAT SWITCHES - WIRING DIAGRAM

SCALE: NONE

BID SET



WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9061
www.wilsonengineering.com



DESIGNED BY BZ
DRAWN BY GH
CHECKED BY BZ


CITY OF FERNDALE, WA
WASHINGTON
PUMP STATION No. 4
PUMP CONTROL WIRING DIAGRAMS

DATE 4/20/2015
SCALE AS SHOWN
JOB NUMBER 2013-037

SHEET E7 OF E11


GENERAL NOTES:

1. THESE SCHEMATICS SHOW ONLY FUNCTIONAL REQUIREMENTS OF THE ELECTRICAL ENCLOSURE. DETAILED WIRING DIAGRAMS, PANEL SIZING AND LAYOUT SHALL BE PROVIDED BY THE CONTROL PANEL SUPPLIER FOR A COMPLETE AND OPERATIONAL SYSTEM.
2. ALL INDICATOR LIGHTS ARE NOT SHOWN. PROVIDE WIRING, INTERPOSING RELAYS AS REQUIRED FOR STATUS INDICATOR LIGHTS FOR ALL SIGNALS SHOWN ON SHEET E6.



PUMP POWER WIRING DIAGRAM
SCALE: NONE

BID SET



DESIGNED BY	BZ
DRAWN BY	GH
CHECKED BY	BZ


CITY OF FERNDALE, WA
WHATCOM COUNTY
WASHINGTON
PUMP STATION No. 4
PUMP WIRING DIAGRAM

DATE	4/20/2015
SCALE	AS SHOWN
JOB NUMBER	2013-037

SHEET	E8
OF	E11




WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9061
www.wilsonengineering.com




GENERAL NOTES:


1. THESE SCHEMATIC SHOW ONLY FUNCTIONAL REQUIREMENTS OF THE ELECTRICAL ENCLOSURE. DETAILED WIRING DIAGRAMS, PANEL SIZING AND LAYOUT SHALL BE PROVIDED BY THE CONTROL PANEL SUPPLIER FOR A COMPLETE AND OPERATIONAL SYSTEM.
2. ALL INDICATOR LIGHTS ARE NOT SHOWN. PROVIDE WIRING, INTERPOSING RELAYS AS REQUIRED FOR STATUS INDICATOR LIGHTS FOR ALL SIGNALS SHOWN ON SHEET E6.



KEY NOTES:


- 1 EXISTING TELEMETRY CONTROL PANEL AND RADIO SYSTEM. RELOCATE TO NEW EQUIPMENT ENCLOSURE. CONNECT ALL NEW INSTRUMENTATION AND SIGNALS TO TELEMETRY CONTROL PANEL PER WIRING DIAGRAMS AND ELECTRICAL PLANS. NEW OPERATOR INTERFACE. PROGRAM PLC AND OPERATOR INTERFACE FOR AUTOMATIC CONTROL OF PUMP STATION.
- 2 PLC AND OPERATOR INTERFACE PROGRAMMING WILL BE PROVIDED BY CITY'S PROGRAMMER, I2 SYSTEMS, UNDER FORCE ACCOUNT. SEE SPECIFICATIONS.
- 3 FLOW METER SYSTEM FM APPROVED FOR CLASS I, DIV 2 HAZARDOUS AREA.
- 4 LEVEL TRANSDUCER FM APPROVED FOR CLASS I, DIV 1 HAZARDOUS AREA.
- 5 PROVIDE INTERPOSING RELAYS TO CONNECT AS SIGNALS SHOWN TO PLC, AS REQUIRED.
- 6 PROVIDE 16 POINT DIGITAL INPUT WIRING EXPANSION MODULE AND INSTALL IN EXISTING PANEL. COORDINATE WITH PROGRAMMER FOR INSTALLATION.






GENERAL NOTE: CONTRACTOR SHALL PROVIDE ALL REQUIRED GROUNDING AND BONDING TO MEET REQUIREMENTS OF NEC ARTICLE 250.

1 GROUNDING SYSTEM DETAIL
SCALE: NONE




TYPICAL HANDHOLE PLAN
SCALE: NONE




TYPICAL HANDHOLE ELEVATION
SCALE: NONE


2 ELECTRICAL HANDHOLE DETAIL
SCALE: NONE



3 GROUND ROD DETAIL
SCALE: NONE




4 STRAIN RELIEF DETAIL
SCALE: NONE




SECONDARY AND FEEDER RACEWAY
SCALE: NONE

- GENERAL NOTES:
1. MAINTAIN 12" MIN. SEPARATION BETWEEN WATER UTILITIES.
 2. PROVIDE 2" SEPARATION BETWEEN MULTIPLE CONDUITS AND NEAREST SIDEWALL.
 3. TRENCH WIDTH TO ACCOMMODATE ALL CONDUITS AND SERVICES. MINIMUM WIDTH 18".
 4. BACKFILL IN ACCORDANCE WITH UTILITY AND CIVIL STANDARDS.
 5. CONDUIT SHALL BE BEDDED W/SAND (3" BASE & 3" COVER MIN).


5 ELECTRICAL RACEWAY AND TRENCHING DETAILS
SCALE: NONE



6 LIGHT POLE BASE DETAIL
SCALE: NONE



7 TELEMETRY ANTENNA MOUNTING DETAIL
SCALE: NONE



8 INTRINSICALLY SAFE RELAY CONNECTION DETAIL
SCALE: NONE

BID SET



NO.		BY		DATE	
<p>WILSON ENGINEERING, LLC 805 DUPONT STREET BELLINGHAM, WA 98225 (360) 733-6100 • FAX (360) 647-9861 www.wilsonengineering.com</p> <p>Wilson SURVEY/ENGINEERING</p> <p>Brian L. Zipsauer STATE OF WASHINGTON REGISTERED PROFESSIONAL ENGINEER 4-20-2015</p> <p>DESIGNED BY: BZ DRAWN BY: GH CHECKED BY: BZ</p> <p>CITY OF FERNDALE, WA WHATCOM COUNTY ELECTRICAL DETAILS</p> <p>DATE: 4/20/2015 SCALE: AS SHOWN JOB NUMBER: 2013-037</p> <p>SHEET: E10 OF E11</p>					

ID	VOLTAGE	CONDUIT	WIRE QTY	SIZE	DESCRIPTION
P-SEB	480/277V	3"	4	#3/0 AWG	SECONDARY - METER BASE TO SERVICE DISCONNECT
P-GEN	480/277V	2"	4	#3/0 AWG	GENERATOR TO AUTOMATIC TRANSFER SWITCH
P-ATS	480/277V	2"	4	#3/0 AWG	SERVICE ENTRANCE BREAKER TO AUTOTRANSFER SWITCH
P-EE	480V	2"	3	#3/0 AWG	ELECTRICAL ENCLOSURE POWER
P-PCP	480V	2"	3	#3/0 AWG	PUMP CONTROL POWER
P-P1	480V	1-1/2"	3	#3 AWG	PUMP NO. 1 MOTOR LEADS
P-P2	480V	1-1/2"	3	#3 AWG	PUMP NO. 2 MOTOR LEADS
P-T1	480V	1/2"	2	#12 AWG	TRANSFORMER T1 POWER
P-GENP	120/240V	1"	4	#12 AWG	GENERATOR BLOCK HEATER/BATTERY CHARGER POWER
P-LT1	120/240V	1"	2	#12 AWG	AREA LIGHT POWER
P-LP1	120/240V	1"	3	#8 AWG	LIGHTING PANEL LP1 POWER
P-TEL	120/240V	1/2"	2	#12 AWG	TELEMETRY PANEL POWER
P-FM	24VDC	1/2"	2	#14 AWG	FLOW METER - REMOTE MOUNT POWER
C-ATS	24VDC	1"	8	#14 AWG	AUTOMATIC TRANSFER SWITCH/GENERATOR STATUS
C-GEN	24VDC	1"	10	#14 AWG	GENERATOR - RUNNING FAIL STATUS, GEN CONTROL, INTRUSION
C-TEL	24VDC	1"	AS REQ'D	#14 AWG	PUMP STATION DIGITAL I/O
S-FM	24VDC	1"	2	FC	FLOW METER - ELECTRODE AND COIL FACTORY CABLE
S-TEL	24VDC	1"	AS REQ'D	#18 TSP	PUMP STATION ANALOG I/O
S-WW1	24VDC	1"	1	#18 TSP	WET WELL LEVEL TRANSDUCER
S-WW2	24VDC	1"	6	#14 AWG	WET WELL FLOATS (BCKUP FLOAT CONTROL)
S-WW3	24VDC	1"	4	#14 AWG	WET WELL FLOATS (HIGH AND LOW LEVEL ALARM)
ANT	---	2"	1	COAX	TELEMETRY RADIO ANTENNA CABLE
ETH	---	1/2"	1	CAT 6	PANELVIEW COMMUNICATION CABLE
FIBER	---	2"	---	---	SPARE - (FUTURE FIBER)

*NOTE: PROVIDE EQUIPMENT GROUNDING PER NEC 250.

CONDUIT SCHEDULE

SCALE: NONE

LIGHTING SCHEDULE							
ID	DESCRIPTION	MOUNTING	LAMPS	VOLTAGE	LUMENS	WATTS	MANUFACTURER
F1	AREA LIGHT, POLE MOUNT	10' POLE	60 LED	120	14,461	134	LITHONIA CSX1 LED, OR EQUAL.

LIGHTING SCHEDULE

SCALE: NONE

PANEL: LP1					PANEL SCHEDULE					PROJECT: City Of Ferndale Pump Station No.4					
120/240V, 1Ph, 3W.					100A Bus			40A M.C.B.			SURFACE MOUNTED				
CKT	DESCRIPTION /	LOAD	LOAD	C.B.	C.B.		C.B.	C.B.	LOAD	LOAD	DESCRIPTION /	CKT			
NO	LOCATION	(VA)	TYPE	AMP	POLE	PHASE	POLE	AMP	TYPE	(VA)	LOCATION	NO			
1	RECEPTACLE - PANEL MOUNT	180	R	20	1	A	1	20	H	1,000	GENERATOR - BATTERY CHARGER	2			
3	PANEL HEATER	250	H	20	1	B	1	20	G	1,500	GENERATOR - COOLANT HEATER	4			
5	PANEL LIGHTING	64	L	20	1	A	1	20	L	500	SITE LIGHTING	6			
7	PUMP CONTROL	1,000	C	20	1	B	1	20			SPARE	8			
9	SPARE			20	1	A	1	20			SPARE	10			
11	SPARE			20	1	B					SPACE	12			
13	SPACE					A					SPACE	14			
15	SPACE					B					SPACE	16			
TOTAL CONNECTED LOAD:		PH A	1,744 VA	14.5 AMPS		DATE: April 16, 2015									
TOTAL CONNECTED LOAD:		PH B	2,750 VA	22.9 AMPS											
MAX PHASE CONNECTED LOAD:		PH B	2,750 VA						PANEL RATING:		10,000 AIC				
TOTAL CONNECTED LOAD (2 x MAX):			5.5 kVA	22.9 AMPS		TOTAL DEMAND LOAD:		4.9 kVA	20.4 AMPS						
		CONNECTED LOADS	SUBFED LOADS [S]	TOTAL LOADS		DEMAND FACTOR		DEMAND LOAD							
G	GENERAL (NON-CONTINUOUS)	1,500 VA	0 VA	1,500 VA		100%		1,500 VA							
L	LIGHTING	564 VA	0 VA	564 VA		125%		705 VA							
R	RECEPTACLES - UP TO 10 KVA	180 VA	0 VA	180 VA		100%		180 VA							
	OVER 10 KVA		0 VA	0 VA		50%		0 VA							
K	KITCHEN	0 VA	0 VA	0 VA		100%		0 VA							
H	HEATING	1,250 VA	0 VA	1,250 VA		100%		1,250 VA							
M	MOTORS	0 VA	0 VA	0 VA		100%		0 VA							
LM	LARGEST MOTOR	0 VA	0 VA	0 VA		125%		0 VA							
WH	WATER HEATER	0 VA	0 VA	0 VA		100%		0 VA							
C	CONTINUOUS (GENERAL LOAD)	1,000 VA	0 VA	1,000 VA		125%		1,250 VA							
N	NON-COINCIDENT	0 VA	0 VA	0 VA		0%		0 VA							
TOTAL:		4,494 VA	0 VA	4,494 VA				4,885 VA							

LIGHTING PANEL SCHEDULE

SCALE: NONE

BID SET



Z Engineers, PLLC
One Fifth Street, Ste 150
Wenatchee, WA 98801
Tel: 509.888.9364
Fax: 509.888.9365
www.z-engineers.com

WILSON ENGINEERING, LLC
805 DUPONT STREET
BELLINGHAM, WA 98225
(360) 733-6100 • FAX (360) 647-9061
www.wilsonengineering.com

DESIGNED BY
BZ

DRAWN BY
GH

CHECKED BY
BZ

CITY OF FERNDALE, WA

WASHINGTON COUNTY

ELECTPUMP STATION No. 4

ELECTRICAL SCHEDULES

DATE
4/20/2015

SCALE
AS SHOWN

JOB NUMBER
2013-037

SHEET
E11

OF
E11